

### **IN THE ABSTRACT OF THE DISCLOSURE:**

Please amend the abstract as follows:

Abstract of the Disclosure:

To maintain a favorable combustion state, ~~by controlling with high response~~ the quantity and quality of a fuel-air mixture to be supplied to cylinders, ~~and thereby to accelerate reduction in the emission level of harmful exhaust containing air pollutants, and reduction in fuel consumption.~~ A mixture supply device used in an internal-combustion engine ~~for automobiles having multi-cylinder combustors,~~ is constructed into the type where motor-driven fuel spraying mechanisms are provided corresponding to respective cylinders, is controlled with a high response. For this purpose, a mixture supply device has a motor-driven exhaust recirculating mechanism for collecting part of the exhaust generated by combustion ~~of a mixture~~ in the ~~above-mentioned~~ internal-combustion engine and then remixing the ~~above-generated~~ exhaust into the mixture, and an integrated controller for transmitting control signals simultaneously to the above-mentioned three types of mechanisms which are built into a motor-driven multiple-throttle mechanism, ~~this.~~ The motor-driven multiple-throttle mechanism being able to operate to control a plurality of air inlet passageways ~~of air flow~~ with one motor, being formed with restrictions of different sizes and shapes in respective inlet passageways, even at the same rotational angle, and being equipped with an air flow control valve capable of accelerating air flow.

~~{Selected Figure} Fig. 3~~